

2SK1190

External dimensions 1 FM20

Absolute Maximum Ratings

(Ta = 25°C)

Symbol	Ratings	Unit
V _{DSS}	60	V
V _{GSS}	±20	V
I _D	±22	A
I _D (pulse)	±88 (T _c ≤ 150°C)	A
P _D	35 (T _c = 25°C)	W
EAS *	17	mJ
T _{ch}	150	°C
T _{tsg}	-55 to +150	°C

*: V_{DD} = 25V, L = 50μH, I_L = 20A, unclamped,
See Figure 1 on Page 5.

Electrical Characteristics

(Ta = 25°C)

Symbol	Ratings			Unit	Conditions
	min	typ	max		
V _{(BR) DSS}	60			V	I _D = 250μA, V _{GS} = 0V
I _{GSS}			±500	nA	V _{GS} = ±20V
I _{DSS}			250	μA	V _{DS} = 60V, V _{GS} = 0V
V _{TH}	2.0		4.0	V	V _{DS} = 10V, I _D = 250μA
R _{e (yfs)}	7.3	11		S	V _{DS} = 10V, I _D = 12A
R _{DS (on)}		0.04	0.05	Ω	V _{GS} = 10V, I _D = 12A
C _{iss}		1300		pF	V _{DS} = 25V, f = 1.0MHz, V _{GS} = 0V
C _{oss}		650		pF	
t _{on}		130		ns	I _D = 12A, V _{DD} = 30V, V _{GS} = 10V, See Figure 2 on Page 5.
t _{off}		60		ns	

